

Universal Robot Loader

MOV650 Q2

Desk Top Automation

MOV650 DTA

**Compact Desk Top
Automation**

MOV650 CDTA

**Site Preparation Guide
Standort Vorinstallations-
Anleitung**

MOV650 DESK TOP AUTOMATION

1 Site Requirements Delivery 1
..... Dimensions 2

Detail	Description
The delivery area	<p>An empty receiving area of 16 m² is required in order to lift the MOV650 DTA from the delivery truck and rotate it for transporting to the site.</p> <p>The wooden crate must be side-lifted only.</p> <p>The delivery truck must have side access.</p>
Site area requirements	<ul style="list-style-type: none">▪ The entrance to the site must be at Least 1,6 m wide.▪ The forklift must have: arms of 1,5 m a minimum loading capacity of 1000 kg <p>The room must be free of dust, dirt and powder of any kind. Specifically: metal or wooden scraps and pieces. Please make sure that the machine is not placed near cutting machines of any sort, grinding machines, sawing machines or any dust making machines.</p>
Floor area requirement	The floor must be capable of carrying 500 kg/m ² .
Minimum height of working area	2.5 m
Ventilation	Not required
Power supply	230 VAC 50Hz or 115VAC 60 Hz

1 SITE REQUIREMENTS

DIMENSIONS

Detail	Description	
Crated dimensions	MOV650 DTA	Length: 2.70 m
		Width: 1.80 m
		Height: 2.30 m
	FLP650	Length: 1.30 m Width: 1.18 m Height: 1.65 m
Uncrated dimensions	MOV650 DTA	Length: 2.50 m
		Width: 1.53 m
		Height: 2.10 m
	FLP650	Length: 1.10 m Width: 0.93 m Height: 1.40 m
Net weight	MOV650 DTA	800 kg
	FLP650	200 kg

The system is delivered with four adjustable feet on each unit. The legs are then adjusted so that they take the full weight of the system.