

## MIVA 2512E T3



Maximum image size: 24 x 28 / 610 mm x 720 mm  
 Minimum film size: No limit

**Resolution**

1/3 mil / 3000 dpi  
 1/6 mil / 6000 dpi  
 1/12 mil / 12000 dpi

**Plotting time for a panel of 18 x 24 (457 mm x 610 mm)**

3.0 min. at 3000 dpi  
 6.0 min. at 6000 dpi  
 12.0 min. at 12000 dpi

**Minimum structure size**

1.4 mil / 35  $\mu$ m

Physical size: H: 40 = 965 mm, W: 53 = 1350 mm, D: 45 = 1150 mm, Weight 330 kg  
 Power requirement: 230 VAC, 50/60 Hz, 250 W or 115 VAC, 50/60 Hz, 250 W  
 Accuracy: -0.5 mil / 12.5  $\mu$ m - absolute  
 -0.25 mil / 6  $\mu$ m - repeatability  
 Technology: XENON-LCD Raster Image Projection Technology  
 Environment: Dependent on film sensitivity - red or green safe light darkroom conditions for film loading  
 Recommended temperature: 20C  
 Recommended humidity: 50%  
 Media: Silver halide film or glass up to 0.25 thick. Red, green or blue light sensitive.  
 User dialogue: Simple instructions for programming and operation by keyboard or optional remote control via network  
 Communications: Local area network, CD-ROM, Floppy Disk  
 Protocol emulations: Gerber, RS 274-X, HP-GL, Fire 9000  
 optional: PostScript, TIFF, PCX, others on request  
 User languages: English, German, French, Spanish  
 User interface: Netlink queue and plot manager (Win 9x, 2000 and XP compatible) runs from anywhere on your host network (optional)

**The Technology**

All MIVA raster photoplotters use a unique plotting procedure, utilizing a XENON flash as a light source and a high resolution spatial light modulator to generate the image. This system projects a clean high definition image onto the film. There are various resolutions available between 3000 dpi and 128000 dpi. The photo head exposes the film during its continuous movement across the film surface. Positioning is controlled in real time by high resolution linear encoders. This makes MIVA photoplotters fast and accurate. The ultra reliable light source allows years of operation with red, green or blue sensitive films or glass plates.

**Photoplotter**  
**Production Class**  
**MIVA 2512E T3**

MIVA Technologies GmbH  
 Benzstrasse 17  
 71101 Schönaich  
 Germany

Telephone: +49 (0) 7031 75600  
 Telefax: +49 (0) 7031 756030  
 E-mail: [info@mivatec.com](mailto:info@mivatec.com)  
 Internet: [www.mivatec.com](http://www.mivatec.com)