

- manual





1.2 Technical Data Sheet

Machine Type:

Alpha Prep

Delivery Date:

Dec 2005

Machine Length
Machine Width
Machine Height
Max. Working Width
Working Height
Working Direction:

[mm]: 5875 [mm]: 1450/1175/960 [mm]: 1090

1090 650 900+/-

[mm]: [mm]:

900+/- 15 Left-Right

Operation Voltage Special Voltage Control Voltage Tot. Connected Power Tot. Connected Ampere [V/Hz]: [V]: 400±10% / 50HZ

[V]:

24 DC 27

[kW]: [A]:

27 64

Sound Level (measured in accordance with DIN 45635 at a free-standing machine)

[dB(A)]:

72

Conveyor Speed

[m/min]:

0,2 - 6,0





RODUCTION TRODUCTION - INT

1. Introduction

1.3 General Description

The Bond process line (oxide replacement) or the black oxide line is a fully automatic system used to chemically oxide the copper surface of the PCB's image pattern. The Bond processes can be also used as a preclaening line. It is most often used in multilayer production. The PCBs pass through the machine horizontally during the process. The entering panel triggers the work process.

The modular construction of a black oxide line typically consists of:

- Input
- Degreasing
- Rinsing
- Micro Etching
- Rinse
- NaOH-Rinse
- Black-Oxide
- Rinse
- Dryer
- Runout
- Separate Control Cabinet

The modular construction of a Bond process line typically consists of:

- Input
- Cleaner
- Cascade-Rinse
- Pre-Dip
- Etch Bond
- Cascade-Rinse
- Acid Cleaner
- Cascade-Rinse
- Dryer
- Output

The control cabinet is located directly next to the line. Transport speed can be infinitely regulated by a potentiometer between 0.2 and 6.0 m/ min. and is monitored by a digital display included. The line accepts boards between 0.2 and 6.0 mm thick.





RODUCTION - INTRODUCTIO

1. Introduction

The Bond process line or black oxide line of the *combi-etch* type can be completely integrated into any line manufactured by Gebr. SCHMID if the working width is the same. It can be loaded and unloaded by all handling systems produced by Gebr. SCHMID (*Vacumat*). Module lengths between 375 and 2725 mm allow for exact fittings according to customer's preference and capacity demands. Additional extensions, modifications and division of the line can be implemented at any time.

The only materials used are PVC with high impact resistance and titanium metal parts. There is no danger of the etching agent crystallizing during standstill periods because the transport system is open in the working area. There are no leaks in the line and it can be disassembled quickly without tools.

The submersible pumps used in the modules are leakproof with inlet from above and below and have an impeller wheel fed from both sides. The pumps thus contribute to the best mixing of the etching agent. The rinse and tank modules available allow the combination of fresh water, recirculated water, and cascade rinsing. Large volume tank modules use the same pumps as the etching module.

Dryers are equipped with slanted suction nozzles above and below the bore holes. There are also squeegee rollers above the conveyor level, vacuum pumps, and air knives. In addition, large dryers have one or more high-powered blowers. The hot air output is thermostatically regulated and therefore can be used for high feeding speeds.

All modules can be delivered in either direction of operation. The following working widths are available:

- 400 mm
- 650 mm
- 1320 mm

